

Flying Probe Tester – G75



G75

24.4" x 20.1" / 620 mm x 510 mm

- **Double sided** Flying Probe system
- **High-speed lead screw driven motion system** - mounted on marble, increases speed and repeatability
- **Pneumatic Clamping** – for thin core material
- **CE Certified**
- Utilizing **FPX software** with all its **features and benefits**
- **Multi image testing** - allows to test multiple jobs on one panel, increasing the output capacity
- **Fully automatic camera alignment system**
- Comes with a **Plug and Play link** with the **Gardien AC8**

PLEASE CONTACT US FOR MORE INFORMATION:

Group
Info.group@gardien.com
+65 6225 2238

China
Info.cn@gardien.com
+86 512 5770 7951

Germany
Info.ge@gardien.com
+49 6431 929730

Japan
info.jp@gardien.com
+81 3 3904 6230

Taiwan
Info.tw@gardien.com
+886 3355 1668

USA
Info.us@gardien.com
+1 (503) 430 8980

Canada
info.ca@gardien.com
+1 (416) 292 0726

Flying Probe Tester – G75

TECHNICAL INFORMATION

No. of test probes	4 (2 front / 2 back) High Speed Z-Axis with soft touch (requires soft touch probes)	
Test probe pressure	2-10 g	
No. of CCD-cameras	2 (1 front/1 back)- Fully automatic camera alignment for easy and fast compensation of board registration	
Max test area (x/y)	24.4"x 20.1"	620mm x 510mm
Min board size (x/y)	2" x 2"	50mm x 50mm
Max board thickness	235mil	6mm
Min board thickness (standard)	10mil	0,25mm
Repeatable accuracy +/-	0.6mil	15µm
Resolution (x/y) +/-	0.6mil	15µm
Smallest testable pad size	3mil	75µm
Smallest testable distance/pitch	3mil	75µm
Board Loading option	Stretch Frame	

OPTIONS

Hardware

- > Quick Frame

Software

- > Data preparation software (Certified Ucamco Smartseat)
- > Verification software (Certified Ucamco FaultStation)

DIMENSIONS & ENVIRONMENTAL CONDITIONS

Width	70"	1780mm
Depth	29.9"	760mm
Height	73.7"	1874mm (w ithout status light)
	87.5"	2223mm (w ith status light)
Weight	1764lbs	800kg

ENVIRONMENTAL CONDITIONS

Air humidity	45-65% not condensing	
Room Temp.	64° -90°F	18°-32°C
Power supply	230V, 50/60Hz, 1000W Single Phase	
Air supply	6 bar oil free	

ELECTRONICS

Test voltage	20V up to 500V (adjustable)
Test current	5mA up to 200mA (adjustable)
Continuity test	2 Ohm up to 2000 Ohm
Isolation test	5 M Ω up to 500 M Ω

SOFTWARE

Operating Software	Windows 10 (English Version)
User Interface	Gardien FPX with multi Language support (Chinese, Japanese, English, German, Spanish)
Data Input formats	MNF1, MNF2, IPC D 356A, , EMMA